



CARATTERISTICHE TECNICHE TECHNICAL DATA

CARICHI LOADS	Portata Nominale / Capacity	400 Kg
	Tiro Funi Max. / Max Cross Loads	740 Kg
	Peso Cabina Max. / Car Weight	250 Kg
	Massa Arcata / Car Frame Weight	90 Kg
	Massa Arcatina / Pulley Assembly Weight	23 Kg

Velocità Max. (Blocchi a Presa Istantanea) Max Speed (Instantaneous Safety Gear)	0,15 m/sec.
Tipo Guide / Guide Type	82/68/9-70/70/9-70/65/9-89/62/16
Nr. Funi(Diametro) / Nr. Ropes(Diameter)	N° 2 ø 8
Pattini tipo / Guide shoe type	a striscio
Diametro Puleggia / Pulley Diameter	ø 320
Diametro Max Pistone "Dp"	
Max Ram Diameter "Pd"	ø90
Profondità fossa Min / Min Pit Depth	100 mm

Pistone con perno di centraggio inferiore ø20
jack with lower pin ø20

Possibilità montaggio tiro funi DX o SX

Draught ropes L or R assembly option

**ARCATA TIPO 501 2:1
CAR FRAME TYPE 501 2:1**

Pagina / Page	1 / 1
Data / Date	12.10.06
Codice / Code	T4ACL001
Edizione / Edition	5,0

TECHNOUFT s.r.l.

LAVIS - TRENTO